

XL MARBLING

Durafloor[®]
House of Vinyl Flooring

SIZE : 304.8 x 304.8mm
THICKNESS : 2.0mm



*Due to technical reasons, colours presented here may vary slightly during production.



TECHNICAL DATA

Size	304.8mm x 304.8mm (Asbesto Free)
Thickness	2.0mm
Packing	50 pieces / carton
Weight	18.8kg / carton
Specification	Manufacture in accordance with Japanese Industrial Standard. JIS 5705 A Of 1990
Resistance to	Cooking oil, Gasoline, Kerosene, Cottonseed Oil, Sodium Hydroxide 2%, Cement Paste

Installation	Subfloor to be smooth, hard, clean and dry prior to laying. Use appropriate adhesive recommended by distributor.
---------------------	---

Maintenance	Once the floor is installed, wipe thoroughly with a damp mop and apply a layer of seal to protect the surface. Daily maintenance is by damp mopping whilst regular cleaning or maintenance schedule should be establish based on your specific traffic.
--------------------	---

Recommended Application	School, Health Care, Public Building, Industries, Restaurants, Supermarkets, Retail Outlets and Offices.
--------------------------------	--

DURATILE XL MARBLING FLOOR TILE

With a reputation for being both practical and economical.

It offers a spectral of commercial floors to meet the durability requirements of institutional and commercial application. Available in a wide range of colours/ designs, they provide the spark for creative interior environments.